



## The trusted independent experts for hand dryers and washrooms since 2012.





## MATERIALS:

Mirror — 18-8, type-304, 20 gauge (0.9mm) stainless steel polished to a No. 8 mirror finish. Mirror has 1/4" (6mm) return.

Backing — 1/4" (6mm) thick tempered masonite.

## **INSTALLATION:**

Mount mirror on wall with four #8 oval head screws, furnished by manufacturer, at points indicated by an *S*. For plaster or dry wall construction, provide concealed backing to comply with local building codes, then secure unit with sheet-metal screws furnished. For other wall surfaces, provide fiber plugs or expansion shields for use with sheet-metal screws furnished, or provide 1/8" (3mm) toggle bolts or expansion bolts.

## SPECIFICATION:

Frameless stainless steel mirror shall be 18-8, type-304, 20-gauge (0.9mm) stainless steel polished to a No. 8 mirror finish. Mirror shall have 1/4" (6mm) return concealing 1/4" (6mm) tempered masonite backing. Four corner countersunk holes provide flush fit of mounting screws with mirror surface.

Mirror shall be Model B-1556 \_\_\_\_\_\_\_ (insert width and height) of Bobrick Washroom Equipment, Inc., Clifton Park, New York; Jackson, Tennessee; Los Angeles, California; Bobrick Washroom Equipment Company, Scarborough, Ontario: Bobrick Washroom Equipment Pty. Ltd., Australia; and Bobrick Washroom Equipment Limited, United Kingdom.

The illustrations and descriptions herein are applicable to production as of the date of this Technical Data Sheet. The manufacturer reserves the right to, and does from time to time, make changes and improvements in designs and dimensions